

Bollard 016

CAST ALUMINIUM | 870 mm



Specifications

Cylindrical bollard with a cylindrical base. Made from polished or painted cast aluminium, as required.

Mounting

Removable with 3p-Technologie, comprising a 300 mm ground shell, junction piece with pre-determined breaking point (without anti-roll device), 1 clamping cone with internal thread, 1 clamping cone without internal thread and a hex head bolt as a standard.

Alternatives: concrete embedment or fold down

Ground rosette option

- Completely covers the ground shell, unauthorised removal is prevented by small hooks
- Material: Steel ST37, hot-dip galvanised and powder coated in bollard colour

For surcharge, see online-shop "Components"

Finish

- Powder coating in standard RAL colours or DB 703
- Accessories and special requirements such as different colours, red and white paint, reflective film or powder coating of chains, rings, shackles, etc. in the same colour as the bollard are available on request at a surcharge.
- For details, see catalogue p. 2-23, price list or online-shop




Colour: DB 703, Design: "hammer.runge design"



	Fixed mounting	3p-Technologie	Fold down
Cast aluminium	016.001	016.020	016.005
Ground rosette	000.031		

Optional rosette



Measurements

Height above ground level: 870 mm

Diameter: 85 mm/98 mm

Height ground shell: 300 mm or 500 mm

Weight: approx. 10 kg (for fixed mounting + 1.5 kg)

