

LIGHTING-BOLLARD 200

Stainless steel | 620 mm

Specifications

Fixed mounting: Cylindrical stainless-steel lighting bollard as permanent fixtures. With satined or clear acryl glass. Reflective slats surround the light unit. With standard lighting. Internal cable plus electric ballast for connection to a 230 Volt (AC) power source. IP Code IP54.

Mounting

Screw-on (fixed mounting)


Finish

- Stainless steel 1.4301 smoothed, grain 240
- Stainless steel 1.4301 with powder coating in standard RAL colours or DB 703
- Available with satined or clear acryl glass
- Supplied with standard Dulux D/E 13 watts TC-DEL lighting (26 watts available on request with a surcharge)
- Lower fitting: hexagon shell safety screws with pin, incl. key

Note

- Including power cable, consisting of a bollard-sided cable with a plug (IP67, 50 cm) and a ground-sided cable with a socket (IP67, 150 cm).
- Technical components for power supply and control are not included. The connection has to be made by the customer.

	Light unit	Acryl glass	Finish	Fixed mounting
Lighting-Bollard 200	standard	Clear	Pickled/smoothed	200.001
Lighting-Bollard 200	standard	Satined	Pickled/smoothed	200.010
Lighting-Bollard 200	standard	Clear	Powder coating	201.001
Lighting-Bollard 200	standard	Satined	Powder coating	201.010



Technical information

(Standard lighting)

- Light unit: Osram Dulux TC-DEL 13 watts
- Connection voltage: 230 Volt AC
- Luminous flux: 900 lm
- Light colour: 830 K (warm white)
- Protection class 1, IP Code IP54



Stainless steel, satined acryl glass

